

Externe Kühl- und Heizeinheit (3. Generation)

Das leistungsstarke externe Kühl-/Heizgerät, das für den Einsatz mit den Avant°pool Hanki & Kide Becken geeignet ist, lässt sich auch problemlos mit anderen Pools, Wannen und Becken verwenden.



Produktmerkmale

- » IPX4-klassifiziert – für den Außenbereich geeignet
- » Integrierte Umwälzpumpe
- » Digitales Bedienfeld
- » Abkühlung auf +4 °C
- » Aufheizen auf +40 °C
- » WiFi-Steuerung
- » Einfache Schnellanschlüsse (32 mm)

Technische Details

| | |
|----------------------------|--|
| Produktname | Avant°pool externe Kühl- und Heizeinheit |
| Artikelnummer | AP.EXCOOLHEAT.001 |
| Maße mit Rädern (L/B/H) | 74 cm x 37 cm x 54 cm |
| Maße ohne Räder (L/B/H) | 74 cm x 37 cm x 49 cm |
| Stromversorgung | 220 - 240 V, 50 Hz |
| Stromanschluss | 6.0 A |
| Kühlleistung | 1,0 kW |
| Kühlgeschwindigkeit | 8 °C/Stunde |
| Heizleistung | 1,0 kW |
| Heizgeschwindigkeit | 8 °C/Stunde |
| Betriebstemperatur | -7 °C bis 43 °C |
| Kältemittel | R32 |
| Wasserbeständigkeit | IPX4 |
| Wasserbindung – Anschlüsse | Schnellanschlüsse (32 mm) |
| Kabel | Netzkabel mit RCD (220 cm) |
| Versandkartonmaße/Gewicht | 82 cm x 43 cm x 52 cm/Gewicht 60 kg |



Gewicht
42 kg



Garantie
2 Jahre (private Nutzung)/
1 Jahr (gewerbliche Nutzung)



Steuerung
WiFi-Fernbedienung (App)



Zertifizierung
CE-zertifiziert

Cooling & Heating unit (3rd generation)

The powerful external cooling/heating device, which is suitable for use with the Avant^opool Hanki & Kide pools, can also be easily used with other pools, tubs and pools.



Product features

- » IPX4 rated – suitable for outdoor use
- » Integrated circulation pump
- » Digital control panel
- » Cooling to +4 °C
- » Heat up to +40 °C
- » WiFi control
- » Simple quick connectors (32 mm)

Technical details

| | |
|-----------------------------------|--|
| Product name | Avant ^o pool cooling & heating unit |
| Product number | AP.EXCOOLHEAT.001 |
| Dimensions with wheels (L/w/h) | 74 cm x 37 cm x 54 cm |
| Dimensions without wheels (L/w/h) | 74 cm x 37 cm x 49 cm |
| Power supply | 220 - 240 V, 50 Hz |
| Current | 6.0 A |
| Cooling capacity | 1,0 kW |
| Cooling/heating speed | 8 °C per hour |
| Heating capacity | 1,0 kW |
| Heating speed | 8 °C per hour |
| Operating temperature | -7 °C bis 43 °C |
| Refrigerant | R32 |
| Water resistance | IPX4 |
| Water connection – connections | Quick connectors (32 mm) |
| Cable | Power cable with RCD (220 cm) |
| Export carton meas./weight | 82 cm x 43 cm x 52 cm/weight 60 kg |



Weight
42 kg



Warranty
2 years (private use)/
1 year (commercial use)



Control
WiFi control



Certification
CE certificated